

L20 B-E



Effort-free cleaning

Available in the version with 1 disc brush of 51 cm

cowos

L20 B-E is suitable for the maintenance cleaning of commercial surfaces up to 1400 sq.m.: guaranteed cleanliness without training



L20 B-E is a walk-behind scrubbing machine available in electric or battery versions, with 1 disc brush of 51 cm working width.



L20 B can work for up to 1 hour over a surface of 2000 sq.m. with a single tank of detergent solution.

Up to 2 hours autonomy with a single energy charge.



The amount of solution can be regulated according to the real cleaning needs.



Access to the battery compartment is quick and easy.
On request, the L20 B models can be fitted with the following batteries:
- 12 V/102 Ah (2)

- Gel 12V/75 Ah (2)

Compared to a traditional scrubbing machine, L20 offers the following benefits:

- It can be used even by untrained operators
- High productivity and reduced consumption levels
- Squeegee made of reinforced, corrosion resistant plastic material
- Easy maintenance at the end of the work
- Easy to move from one place to another
- The brush head made of aluminum is robust and corrosion resistant



comos

L20 is easy to use, transport and sanitise



L20 B-E is fitted with a new squeegee in a reinforced (Patent Pending) plastic material that is corrosion resistant. The automatic uncoupling system protects the squeegee when accidentally impacted.



With L20 B-E, you're ready to work at once!

Just:

1. Fill with the detergent solution - 2. Lower the squeegee - 3. Switch on the machine and the vacuum function - 4. Start working









Maintenance is easy and effort-free. That means machine efficiency is guaranteed over time!









On request, the L20 B can be fitted with on board battery charger, so that recharging operations are quick and simple to perform

L20 B-E perfect cleaning along walls





Automatic brush coupling and uncoupling



L20 B-E equipped with solenoide valve

The solenoid valve automatically stops the flow of water when the machine is not working or is stopped by the operator

STANDARD EQUIPMENT L20 B-E

With PPL 0,6 brush of 51 cm

Solenoid valve

Solution filter

Squeegee of 68 cm

TECHNICAL DESCRIPTION		L20 B	L20 E
TECHNICAL DESCRIPTION		L20 D	LZU L
Squeegee width	mm/inch	680/26,8	680/26,8
Disc brushes Ø	(n.) mm/inch	(1) 510/21	(1) 510/21
Brush motor	V/W	24/560	220-230/750
Brush rpm	rpm	135	121,5
Brush pressure	kg/lbs	27,5/60,6	27,5/60,6
Suction motor	V/W	24/310	230/450
Type of drive	-	semi aut.	semi aut.
Battery compartment dimensions (L x h x w)	mm/inch 330 x 2	270 x 345/13 x 10,6 x 13,6	-
Max gradient at full load	0/0	2	2
Batteries	V/Ah C20	12 V/102 (2)	-
Batteries weight	kg/lbs	54/119	-
Machine weight (without battery)	kg/lbs	62/136,7	62/136,7

comoc	Working width mm/inch	Brush pressure Kg/lbs	Power supply V/traction Voltage V/Frequency Hz/ traction	Solution tank I/gal	Recovery tank I/gal	Working capacity up to sq.m/h/sqft/h	Machine dimensions mm/inch L x H x W	Machine weight kg/lbs (without batteries)
L20 B	510/21	27,5/60,6	-/24/semi-aut.	40/10,6	40/10,6	1600/17222	1165/45,8 995/39,2 541/21,3	62/136,7
L20 E	510/21	27,5/60,6	230/50/semi-aut.	40/10,6	40/10,6	1600/17222	1165/45,8 995/39,2 541/21,3	62/136,7











COMAC spa Via Maestri del Lavoro, 13 37059 Santa Maria di Zevio - Verona - Italy Tel. +39 045 8774222 - Fax +39 045 8750303 on line: www.comac.it - e-mail: com@comac.it