



SmartBladeCompact, Swift and Precise


2 MESSER SmartBlade 3

SmartBlade

Compact, Swift and Precise



The Global control guides you in all directions so you can start cutting each job quickly and easily




The swift arc voltage control coupled with the Messer knowhow of plasma dynamics yield precisely cut shapes.



Special ducting software transform smartblade into dedicated sheet metal duct cutting machine








The agility of the machine & precision makes complex profiles easy to cut

SmartBlade MESSER KNOW-HOW YOUR PRECISE OUTPUT

- German quality at a competitive Indian price means value for money.
- Compact design reduces space requirements.
- Positioning speed of 12 m/min reduces idle time between cuts.
- Easy access to the cutting bed from all sides permits quick and efficient unloading and reloading reducing idle time between plates.
- Specially designed slag trays for easy table cleaning and efficient extraction.
- Global Control, the most user-friendly touch-screen control on the market means: Easy operation, from loading program to cutting in only 3 steps.
- Collision recognition (e.g. with tilted part) plus magnetic torch holder for plasma reduces risk of torch damage.
- Reliable height control via arc-voltage control improves nozzle life and cut quality for plasma.
- Machine is supplied as "Drop & Cut" which means no installation time & expense.
- Fume Extractor available on request.

MESSER SmartBlade

Technical Data (dimensions in mm) Working Dimensions 1500 mm width X 3000 mm length Working Height: 700 mm Positioning Speed: 12m/min Plasma Possibilities: Hypertherm Powermax 45/65/85/105/125 or Kjellberg CutFire 100i Machine Foot Print: 2500 mm Width X 5000 mm length Maximum Plate Weight: 47 kg/m² corresponds to structural steel of t=6mm



The descriptions, technical data and illustrations contained in this document are provided for guidance purposes only and are non-binding. The manufacturer reserves the right to make alterations to products without notices.

IM09A0003A21





