PIXEL LED

RO Series





Pai	-+	N	т	m	h	0	r
па		N	ш	ш	ю.	•	и

Pixel pitch LED type

Pixel configuration

Size of module

Resolution of module

Density(dots/m²)

Cabinet material

Size of cabinet(mm)

Weight of cabinet

Support hanging or not

Max power consumption

Average power consumption

Colors

Gray scale

Color temperature

Driving method

Refresh frequency

Brightness

Brightness control

IP grade

RO4/RO(C)4

4.8mm

SMD2727(White)

1R1G1B

192mmx192mm

40x40

42539 Die-casting

576mmx576mm

12.5KG

Yes

750W/m²

250W/m²

16.7M

14bits

3000-10000K 1/11 scanning

1920Hz

4500cd/m² 256 grade

IP65

RO6/RO(C)6

6mm

SMD2727(White)

1R1G1B

192mmx192mm

32*32

27777

Die-casting

576mmx576mm

12.5KG

Yes

750W/m²

250W/m²

16.7M

14bits

3000-10000K

1/8 scanning

1920Hz

5000cd/m²

256 grade

IP65

FOR ANY QUERY - WRITE TO US AT SALES@PIXELLED.IN, PIXELLED.INDIA@GMAIL.COM SALES: +91 9990605900, TECHNICAL - +91 9999599925

SALES: +91 9990605349, 9990605948, 9990605999, 9990700799