



MULTI DECK CHILLER WITH DOOR (PLUG IN)

Blue Star Model			
Export Model		GR-13PWE.2	GR-19PWE.3
Factory Model		IVC2/75WGA	IVC3/75WGA
PERFORMANCE & CONSUMPTION			
Net capacity	(L)	700	1080
Display area		1.2	1.81
Temperature	°C	-1~7°C	-1~7°C
Climate		4 (30 Deg C 55 % RH)	4 (30 Deg C 55 % RH)
Voltage / Fequency	V/Hz	220/50	220/50
Refrigerant		R404A	R404A
Power consumption	[kWh/24h]	6.5	10.7
Compressor type		Recip	Recip
Refrigerant Quantity	KG	0.850	0.950
Refrigeration Capacity	Watts	835	1160
Evaporating	°C	-10	-10
Compressor		HUAYI- Cubigel ML90TG	HUAYI- Cubigel MP12RB
Cooling System		Ventilated	Ventilated
KEY FEATURE			
Condenser		Copper pipe with Fin evaperator	Copper pipe with Fin evaperator
Evaporator		Copper pipe with Fin evaperator	Copper pipe with Fin evaperator
Condensor motorfan		EBM	EBM
Evaporator motorfan		SAIWEI	SAIWEI
Expansion valve		SANHUA	SANHUA
Temperature Control	Optional	Yes, electronic controller	Yes, electronic controller
Interior		Powder coated	Powder coated
Light	Fluorescent/LED	LED	LED
Glass door		Plastic/Self-closing/Double-Low-	Plastic/Self-closing/Double-Low-E
Shelves		5shelves/ 450mm Wire	5shelves/ 450mm Wire
Basket/Shelf QTY		12	12
Adjustable Thermostat		Yes, electronic controller	Yes, electronic controller
supports	n°	4pcs (M18)	6pcs (M18)
Drainage		Self evaperated	Self evaperated
Inner tank bottom	n°	Prepainted Steel	Prepainted Steel
Drawing type condensing unit		yes	yes
DIMENSIONS & LOADABILITY			
Shelf dimension	W*D(MM)	580*400	580*400
Net Dimension	W*D*H	1220*750*1930	1830*750*1930
Packing Dimension	W*D*H	1295*845*2065	1905*845*2065
Weight	N/G (Kg)	218/233	305/330
Loading Quantity	40'HQ	16	12

