



▲ The pinch roller assembly adopts the Eco solvent machine pinch roller structure, which makes the picture combination more precise, the stitching is more perfect, and the fan power is larger;



▲ Intelligent infrared drying system, printing start/stop, infrared automatic open and close;




▲ The feeding system adopts built-in movable media fixing structure to prevent the material from deviation;



▲ Standard negative pressure system, continuous printing without nozzle missing;



▲ Adopting reflective photoelectric switch, capable of printing on black banner ;



▲ The print head anti-collision system can effectively prevent head damage during printing.

C8 PLUS (HS 1000 8 head)		
1pass	360×360dpi	600m <sup>2</sup> /h
1pass	480×360dpi	480m <sup>2</sup> /h
2pass	360×720dpi	280m <sup>2</sup> /h
2pass	480×720dpi	240m <sup>2</sup> /h
C8 PLUS (KM512i-30PL 8 head)		
2pass	360×360dpi	280m <sup>2</sup> /h
3pass	360×540dpi	180m <sup>2</sup> /h
2pass	480×360dpi	240m <sup>2</sup> /h
3pass	480×540dpi	140m <sup>2</sup> /h

C8 PLUS Technical Specifications		
Model	C8 PLUS	
Head Model	KM512I-30PL	KM-HS1000/6988H
printhead quantity	8	8
Drop volume	30PL / 13PL	
Drying system	Infrared- heater fan	
Print width	3300mm	
Rip software	UltraPrint / MainTop / Photo Print / PrintFactory	
Electricity requirement	220v/60A/50HZ	
Machine max power	13295W	9095W
Printing system	1145W	1145W
Front&rear heater	3750W	3750W
Infrared heater	8400W	4200W
Machine package size	5000(L)*1050(W)*1630(H)mm	
Machine body size	4840(L)*940(W)*1400(H)mm	
Gw (kg)	1135KG	1135KG
Nw (kg)	1035KG	1035KG

\*Specifications are subject to change without prior notice, all rights reserved