

MOISTURE ANALYZER



Manufactured in Poland

MODEL	ATS 60	ATS 120	ATS 210	BTS 110D	BTS 110
CAPACITY (GM)	60	120	210	110	110
RESOLUTION (GM)	0.001	0.001	0.001	0.005	0.01
MOISTURE RESOLUTION	0.01%	0.01%	0.01%	0.05%	0.1%
PAN SIZE (MM)	x 90				
HUMIDITY MEASURE REPEATABILITY	±0.1% (Sample 2g) ±0.04% (Sample 5g)		±0.5% (Sample 2g) ±0.2% (Sample 5g)		
HUMIDITY READOUT PRECISION	1% <0.5g sample, 0.1% <5g sample, 0.01% > 5g sample		0.1% (sample > 10g) 1% (sample > 10g)		

Option Accessories



Thermometer



Printer



Disposable



di-sodium



external calibration

GLP compatibility



printout config.

date / time



drying programs
memory

drying graph



Percentage Weighing

drying profiles



multilanguage

drying reports



freeware computer
program

Features

- ★ Halogen heaters.
- ★ Graphical display with back-light & Drying chart displaying.
- ★ Convenient and Easy text menu.
- ★ Reports edition with PS2 PC keyboard.
- ★ Equipped with USB & RS232 Interface.
- ★ Storing 20 drying programs.
- ★ Free PC Software.
- ★ Multiple profiles and analysis modes.
- ★ Drying Report Printing with GLP/GMP.
- ★ Available ways to evaluate humidity:
 - in proportion to initial weight
 - in proportion to dried weight
 - percentage of dried weight
- ★ Drying mode:
 - Time Mode & Short (Auto) Mode.
- ★ Drying Profiles:
 - Standard
 - Fast
 - Slow