



Horizontal Pillow Wrapping Machine

• Feeding System	Automatic and Manual
• Sealing Type	Centre Seal / 4 Side
• Packaging Size	Upto 300mm(L), 180mm(W), 100mm(H)
• Packaging Speed	0 - 200 pouches per min. Variable
• Packing Material	Any Heat Sealable Laminated Film & BOPP Film



• Power (W)	3KW, 1HP AC with AC Drive,
• Voltage (V/Hz)	220 AC (Single Phase)
• Heater Load	400W x 2 Nos., 200W x 2 Nos.
• Dim. LxWxH (mm)	1800 x 1080 x 1700mm
• Approx Weight	700 Kg
• Optional Attachment	Batch Coding Machine


Hot Ink Coder (Intermittent Coder for VFFS Packing Machines)

• Print Area	4 Lines
• Print Speed	Up to 80 Prints/Min.
• Print Lines	T - Type < 4 Lines, Max. 20 Characters/Line
• Font Size	T - Type Character 3.5mm (Height) x 1.5mm, 2.0mm, 2.5mm (Width)
• Control Box	LED Display
• Ink Roll Size	Φ 36x32, Φ 36x40 (mm)
• Power Supply	Ac 220 ± 10V, 50/60 Hz, 2A 130W
• Working Temp.	4°C-40°C, 10%-95% Humidity
• Weight	Print Head - 4.0 Kg - Control Box 1.5 Kg




Motorised Ribbon Printer (Online Ribbon Printer)

• Voltage	AC 220/50
• Power Supply	150W
• Print Speed	0-200 Times/min.
• Print Area	4 Lines (Max. 15 Characters/Line)
• Font Size	3mm
• Printing Media	Hot Foil (Available in Various Colours)
• Prints Method	Brass Characters
• Weight	7 Kg (Without Stand)



Pneumatic Ribbon Printer (Online Ribbon Printer)

• Power Supply	220V/50Hz
• Driven Type	Pneumatic
• Print Area	4 Line Max. 15 Characters/Lines
• Print Speed	0-200 Times/Min.
• Printing Media	Hot Foil (Available in Various Colours)
• Font Size	8.5 PT, 9.5 PT, 10.5 PT
• Colour Ribbon Width	25, 30, 35
• Print Method	Brass Characters
• Weight	7 Kg (Without Stand)



Electro Pneumatic Contact Coder

• Printing Area	25mmx35mm (Other Size can be Manu. on demand)
• Printing Speed	Up to 150 Prints/min.
• Printing Media	Anti Freeze Fast Drying Liquid Ink. (Available in Various Colour)
• Inking System	Special Rechargeable Ink Roller/Cartridges
• Power Supply	230/250 VAC 10% 50Hz Single Phase
• Ink Change	10,000 to 20,000 Impression per 20 ml. Change Ink
• Printing Method	Rubber / Polymer Stereo
• Weight	Approx. 15 Kg



Canny Coverage
PACKAGINGS PVT. LTD.

REGD. OFFICE (SURAT) :
"COVERAGE HOUSE", Plot No. 60 & 117, 118,
Ram Krishna Industrial Co. Op. Society,
Bh. Ranchhod Nagar & Udhna Academic College,
Udhna, Surat - 394 210 (Guj.) India.
Tel. : +91 261 2272421, +91 83062 26664
+91 78786 16664, +91 80009 16664

FACTORY (SURAT) : Plot No. 1068, Sardar Chowk, G.I.D.C., Sachin, Surat - 394 230 (Guj.) India.
BRANCH OFFICE (MUMBAI) : APMC, Vashi, Navi Mumbai - 400 703. (Mah.) India. Tel. : +91 72268 76666
FACTORY (MUMBAI) : Universal Estate Premises Co. Soc. Ltd., Gala No. 3 to 13B, Mogra Vill. Rd.,
Andheri (E), Mumbai - 400 053 (Mah.) India.

For more information Call : +91 93744 31246, +91 93747 35450, +91 93221 27132 or you can
visit us at www.cannycoveragepackagings.com or Mail : inquiry.cannycoverage@gmail.com

Follow us on :
f t i s

Packaging Solutions That Matter

Canny Coverage efficiency with technology for measurable result



Download QR Code Scanner from Google Play
Store scan this code for our demonstration



The most flexible way, to get compact



Canny Coverage
PACKAGINGS PVT. LTD.

AN ISO 9001:2015 CERTIFIED COMPANY

High Speed Stacker

Friction Paging Machine	8001	8005
Voltage (V/Hz)	AC 220/50	
Power (w)	180	
Size Separated Item (mm)	40 - 320	40 - 320
Width (mm)	65 - 280	65 - 430
Thickness (mm)	0.02 - 5	0.02 - 5
Smart Adjustment Mode	Yes	
Speed Adjustment Mode	Imported Frequency Stepless Speed Adjustment	
Speed/Min.	60 - 600 Pcs/Min.	



Conveyor for Inkjet Printer/
Loading Unloading Conveyor

Voltage (v/Hz)	220/50 1 ph
Motor Power (w)	60 Watts A/C Variable
Speed (M/Min.)	0 - 15 Meter/ Per Min. (Speed Adjustable)
Max. Loading Weight (Kg)	≤ 50 Kg
Length & Width (mm)	L-1500mm x W-400mm x 750mm
Distance to Floor	780mm
Dimension (LxWxH)	1500mm x 400mm x 750mm
Net Weight (Kg)	19 Kg



Continuous Band Sealer

	Horizontal	Vertical
Voltage	AC 220/50 110/60	
Motor Power	50	
Sealing Power	300 X 2	
Speed	0 - 12	
Sealing Width (mm)	12mm	
Temperature Range	0 - 300	
Distance for Sealing Center	10mm - 40mm	150mm - 270mm
Conveyor Table Size	L : 840mm - W : 153mm	
Overall Conveyor Loading	± 3	
Dimension	840 x 380 x 320mm	840 x 380 x 550mm

Application : Special for Masala, Pharma, Surgical, Oil etc.



Continuous Band Sealer with Nitrogen Flushing

Power Supply	Single Phase 220V/50Hz
Power Consumption	500W
Sealing Speed	0 to 12 Mtr./Min.
Sealing Width	10mm
Temperature	0 to 300°C
Conveying Load	3 Kg
Dimension	1040mm x 380mm x 1450 to 630 Adjustable (mm)
Weight	40 Kg

Application : Namkeen, Tobacco, Spices, Detergent Powder, Instant Food, Bakery, Chemical, Flour Mills, Pharma, Dairy Product etc.



Heavy Duty Continuous Band Sealer

	Horizontal	Vertical
Voltage	AC 220/50 110/60	
Motor Power	50	
Sealing Power	300 x2	
Speed	0 - 12	
Sealing Width (mm)	12mm	
Temperature Range	0 - 300	
Distance for Sealing Center	10mm - 40mm	150mm - 270mm
Conveyor Table Size	L : 840mm - W : 153mm	
Overall Conveyor Loading	± 3	
Dimension	840 x 380 x 320mm	840 x 380 x 550mm
Weight Kg	32	37

Application : Special for Masala, Pharma, Surgical, Oil etc.



Continuous Band Sealer (1 Kg to 10 Kg)

Voltage	AC 220/50 110/60 V/Hz
Motor Power	100W
Sealing Power	320 x W
Speed	0 - 12 Mtr./Min.
Sealing Width	10mm
Temperature	0 to 300°C
Distance from Sealing Center to Conveyor	100mm - 500mm
Conveyor Size	1250mm x 225mm
Max. Conveyor Load for Single Bag	5 Kg
Overall Conveyor Load	15 Kg

Application : Special for Masala, Pharma, Surgical Oil etc.



Big Vertical Continuous Sealing Machine

Sealing Width	10 - 13mm
Sealing Speed	6 Mtr. per min.
Max. Conveyor Load	25 Kg
Conveyor Belt Width	200mm
Temp. Range	0 - 300°C
Mic. Dim. LxWxH (mm)	1540 x 925 x 1515mm
Voltage	50Hz 10 220V / 5A
Approx Weight	150 Kg
Optional	Gas Flushing Attachment

Packing Material : Any heat sealable material like PP, LD, LLDPE, HMHD, Alu. Foil and any laminated 2 or 3 layer pouches



Heat Shrink Packing Machine Leg Type

Mechanical Dim. LxWxH (mm)	1200 x 720 x 880mm
Temp. Range	300°C max.
Voltage	50Hz 30-440v + N + E
Tunnel Dim. LxWxH (mm)	1170 x 425 x 250mm
Heater (KW)	6 KW
Motor	1/4 HP Gear Motor + 1/4 HP
Conveyor Speed	Variable Max. 8 Mtr. per min.

Heat Shrink Packing Machine Table Top

Mechanical Dim. LxWxH (mm)	750 x 450 x 630mm
Temp. Range	250°C max.
Voltage	50Hz 30-440v + N + E
Tunnel Dim. LxWxH (mm)	430 x 100 x 100mm
Heater (KW)	3 KW
Motor	1/10 HP Gear Motor + 1/10 HP
Conveyor Speed	4 Mtr. per min.



Heat Shrink Packing Machine for LD Film

Mechanical Dim. L x W x H (mm)	2000 x W-650 x H-800mm
Temp. Range	350°C max.
Voltage	50Hz 30-440v + N + E
Tunnel Dim. L x W x H (mm)	1200 x W-500 x H-500mm
Heater (KW)	8 KW
Motor	1/4 HP Gear Motor + 1/4 HP Blower Motor 2 Nos.
Cooling Fan	2 Nos.
Conveyor Speed	Variable Max. 10 Mtr. per min.

Web Sealer with Shrink Tunnel

6540 (Web Sealer)	
Voltage	AC 220/50 (V/Hz) - 110/60 (V/Hz)
Power	1.5 (KW)
Max. Packing Size	L : 550mm x W : 400mm x H : 380mm
Max. Sealing Length	650mm
Working Air Pressure	5-7 (Kg/cm2)
External Dimension	L : 925mm x W : 1040mm x H : 1520mm
Weight	300 Kg
55040 M (Shrink Tunnel)	
Voltage	AC 220/60 (V/Hz) - 380/50 (3Ph)
Power	23 (KW)
Load	40
Conveying Speed	0 - 8
Tunnel Size	L : 1450mm x W : 550mm x H : 400mm
External Dimension	L : 2550mm x W : 850mm x H : 1600mm
Weight	300 Kg



Conveyorize L Sealer Machine

Voltage (V/Hz)	240/50 (Single Phase)
Motor	1/10 HP Gear
Sealing & Cutting Size (mm)	400 x 400mm
Conveyor Speed	6 Mtr./min.
Dim. LxWxH (mm)	1250 x 900 x 1100mm
Sealing Technology	Impulses



Manual Induction Sealer

Machine Size	268mm x 270mm x 100mm
Power Supply	110v 220v/50Hz
Power	500W
Sealing Diameter	0 - 130mm
Weight	4 Kg

Application : Special for Pickles, Pharma, Oil, Ghee, Automobiles, Fertilizer etc.



Automatic Induction Sealer

External Dimension	L - 1150mm x W - 480mm x H - 400mm
Voltage	V/Hz - AC 220/50 110/50
Power	1500W
Sealing Diameter (mm)	Φ20 - Φ50, Φ50 - Φ130
Available Height	40 - 200
Speed (mm)	0 - 10
Production Capacity (Pcs/Min.)	100 (Φ40mm Flat Capped and PE Bottle)
Weight	38 Kg

Application : Special for Pickles, Pharma, Oil, Ghee, Automobiles, Fertilizer etc.

