

DRYER DR-2







DESCRIPTION

- DR-2 IS SUITABLE FOR DE-WATERING AND DE-OILING PURPOSE.
- IT HAS FAST ROTATION WITH VARIABLE SPEED FOR MAX WATER DRAIN AND OIL DRAIN.
- MANUAL AND AUTOMATIC FUNCTION ARE GIVEN WITH FRONT REMOTE CONTROL.
- ALL TIMING OF ROTATION IS ADJUSTABLE AS PER PRODUCT REQUIREMENT WITH DIFFERENT SPEED BY CONTROL PANEL.
- YOU CAN SET TIMING FOR ROTATION OF DRUM IN PROCESS AS WELL AS YOU CAN SET TIME FOR EMPTY BOWL IN DOWN POSITION DRUM WITH FIXED LOW SPEED.
- BODY STRUCTURE FABRICATED WITH 6MM THICKNESS OF STAINLESS STEEL GRADE 304.
- MANY OF PRODUCTS CAN BE USE WITH DR-2 IN DE-WATERING LIKE POTATO SLICE, POTATO STICKS, SEED, PULSES, LEAFS, CUT VEGETABLES, ETC.
- DR-2 IS ALSO SUITABLE TO DE-OILING PROCESS IN MANY SNACKS PROCESSING COMPANIES.

PRODUCTION	MOTOR	DRUM SIZE	DIMENSIONS (H * W * L)	WEIGHT
50 K P/B	7.5 HP(5.5 KW)	23" DIA X 15" H	40×48×55 Inch	450 Kg (990lbs)



HARIKRISHNA TECHNO (INDIA)

Mobile: +91 99796 01809 / +91 94282 64944
Email: hktexports@gmail.com
Website: www.harikrishnaexport.com