



Gear Trolley



Model		GCL0.5	GCL1	GCL1.5	GCL2	GCL3	GCL5	GCL10
Capacity	t	0.5	1	1.5	2	3	5	10
Test Load	t	0.735	1.471	2.206	2.942	4.413	6.129	12.258
The Smallest crankle radius which can gate through	m	0.9	1	1	1.1	1.3	1.4	1.7
Dimensions	mm	A	242.5	245	279.5	179.5	344	362
		B	170	206	228	240	282	327
		C	187	206	236	243	321	393
		H	105	109	125	133	179	220
		F	-3	-3	-3	-3	-3	-3
I-Steel Available	mm	68-94	68-100	88-118	94-124	116-140	142-180	142-180
Net Weight	Kg	11.8	14.7	17.5	17.5	34.5	53	88

Pull-Push Trolley



Model		GCT0.5	GCT1	GCL1.5	GCT2	GCT3	GCT5	GCT10
Capacity	t	0.5	1	1.5	2	3	5	10
Test Load	t	0.735	1.471	2.206	2.942	4.413	6.129	12.258
The Smallest crankle radius which can gate through	m	0.9	1	1	1.1	1.3	1.4	1.7
Dimensions	mm	A	177	194	235	235	275	338
		B	170	206	228	240	282	327
		C	187	206	236	243	321	393
		H	105	109	125	133	179	220
		F	-3	-3	-3	-3	-3	-3
I-Steel Available	mm	68-94	68-100	88-118	94-124	116-140	142-180	142-180
Net Weight	Kg	4.8	7.7	12.8	12.8	34.5	43	88

Beam Clamp



Item No	Capacity (ton)	Flange width (mm)	Dimensions(mm)												NW (kg)
			A	B		C	D	E	F		G	H	I		
				Max.	Min.				Max.	Max.			Min.	Max.	
BC1	1	75-230	246	186	350	66	4	215	133	90	44	20	14	21	4.1
BC2	2	75-230	246	186	350	74	6	215	133	90	44	20	14	21	5.0
BC3	3	80-320	320	232	455	102	8	255	195	143	75	22	30	34	10.4
BC5	5	90-310	310	242	445	110	10	255	193	145	75	28	30	34	120
BC10	10	90-320	320	268	480	118	12	275	185	133	66	28	34	35	18.8

OPTIONAL EXTRA • Can be supplied with shackle



Hand Puller

Technical Data

1 Ton Double Hook	4.5 - 1.8
2 Ton Double Hook	9.8 - 4.8
3 Ton Double Hook	5.1 - 3.3