



Technical Specifications

| Model | Gethray S85 |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Print Head | Konica Minolta 512i – 30 PL |
| Printing Technology | Piezo Electric Inkjet, Drop on demand |
| USB Print Interface Print width | USB 2.0 3200mm (126 Inch) |
| Media Type | Self-adhesive vinyl/Flex/One way-vision/Star flex |
| Media /Ink transmission | Negative Pressure and Auto take-up system |
| Printing Resolution | 720dpi |
| Parts details | BYHX-A Type/UMC Electronics Lead shine / Lead shine DC Servo Motor HIWIN leaner guide Solenoid Valve Germany IGUS Cable DC Ink Pump |
| RIP Software | Ultra Print /Photo print/Honsoft Software |
| Input Power | 03 KVA Online UPS True Shine Wave 06 batteries according to backup AC 220V~(+10%)>15A, 50 Hz/60 Hz |
| Operation Environment | Temp. 20~28°C Humidity: 40~60% Air Conditioner compulsory (1.5 Ton) Separate ground earthing (0-5V) |
| Computer configurations | i5 or i7 Processor WIN 7 (64 bit), 8/16 GB RAM, 01 TB HDD SATA Quick heal anti-virus |
| Other Features | Rear-Bed-Front head heater LED Lights at Cleaning position Printing bed 4 in 1 heating control system Lift type Carriage Unique Print head protection stack |
| Output Printing Speed Machine size | 2 Pass-1200/ 3 Pass-900/ 4 Pass-600 sqft/hour $4.71 \times 1.15 \times 1.58M$ o change without prior notice. We shall not be liable for technical or additional errors or omission contained herein. |