


Standard Specification

Item		Small characters
		UX-D160WG
Nozzle size		65µm
Max. print line number		Up to 6 lines
Maximum number of print characters		Up to 240 characters (Option: Up to 1,000 characters)
Font (Horizontal x Vertical)	4x5	✓
	5x5	✓
	5x7(8), 9x7(8)	✓
	7x10	✓
	10x12	✓
	12x16	✓
	18x24	✓
	24x32	✓
	30x40	✓
	36x48	✓
Character height		2-10 mm
Display & input device		WYSIWYG design
		Display: TFT LCD (10.4" color), backlight provided Input device: Touch panel, input sound provided
Screen language		English
Maximum print rate (Characters per second) (Font 5x5, space 1, 1 line)		Up to 1,148 (Option: Up to 2,563 *)
Standard characters		Alphanumeric A-Z, a-z, 0-9 , symbols (27) and space: Total 90
User pattern		200 patterns each for dot matrix (50 patterns for 30×40 and 36×48 fonts)
Print functions		Calendar, Count, Font mixture
Barcode printing		code39, ITF, NW-7, EAN-13, EAN-8, UPC-A, UPC-E, code128/EAN-128, GS-1 DataBar
2D code printing		Data Matrix (Alphabet: 49 characters/Numerals: 98 characters), QR, Micro QR code
Message storage capacity		300 messages [Option: Up to 2,000 messages (Depends on data content)]
Input signal		Print target detection, Printing stop, Rotary encoder pulse, Reciprocatve printing, Remote control (Run, Stop, High-voltage ON/OFF, Reset), (NPN/PNP Selectable)
Output signal		Print in progress or Print complete, Online(NPN/PNP Selectable), Print ready, Fault, Warning(NPN Only)
Data interface		RS-232C at baud rates selectable up to 115,200bps (Option: Ethernet (Modbus communication))
External memory		USB for user data storage
Head cable length / angle		4m (in-line/90 degrees)
Operating temperature range		0-50°C (1067K Ink)
Operating humidity range		30-90% RH (No condensation)
Power supply (Automatic voltage selection)		AC100-120/220-240V±10% 50/60Hz 120VA
Approval		CE, UL, cUL, C-Tick, FCC, ICES
Dimensions (Width x Depth x Height)		400 x 320 x 527 mm
International protection		IP65
Approximate weight		27kg

\*1 Ink types and temperature are limited.



Information in this brochure is subject to change without notice.

 **Hitachi Industrial Equipment Systems Co., Ltd.**

For further information, please contact your nearest sales representative.



Premium Coding Solutions

**Premium Coding Solutions**

UG-02, Classic Diamond ,WB-94, Sch.No.94,  
Viajay Nagar,Indore (M.P)-452010.

Email Id - sales@premiumcodingsolutions.in | Website -www.premiumcodingsolutions.com  
Mob No.9109958391



Registration number: JQA-QMA12087  
Registration date: April 1, 2005

The Marking Systems and Hoist Systems Division  
(Taga Division) of Hitachi Industrial Equipment  
Systems Co., Ltd. obtained international standard  
ISO 9001 certification for the quality assurance of  
the Ink Jet Printer contained in this brochure.

**HITACHI**  
Inspire the Next

*Ink Jet Printer*

**UX-D160WG**




# The world leader in coding

Hitachi, which manufactured the first Japanese industrial inkjet printer in 1975, has boasted of a high achievement worldwide ever since, not to mention the Japanese market, as a reliable and leading brand of coding.



Hitachi industrial IJ printers are manufactured with the know-how and technology that have been accumulated since 1975 in Hitachi City where Hitachi was first founded. After production, all printers have to pass Hitachi's strict quality management before shipment. We provide quality products to our customers worldwide.



Use of cartridge-type ink and makeup makes the printer easier to use, more convenient, and more resource saving




Easy and quick replacement of ink and makeup cartridges without "getting your hands dirty" or "ink spillage".



Eco-friendly because the ink and the makeup fluid in the cartridge can be consumed right up to the last drop.


It is not necessary to stop the production line to replace the cartridges. An eco-system of a simple cartridge-type bottle can be replaced after the ink or makeup fluid is completely consumed and is also easily disposed of.



Icons on the screen indicate remaining amount of the ink and makeup. They also indicate the proper time for cartridge replacement, which further improves usability.




The stainless steel cabinet offers IP65 and allows a wash-down with pressured water and industrial detergent, to meet any environment and hygiene requests. The UX Series with IP65 protection is the ideal choice for applications in the meat and dairy sectors.



Tapered shape at the tip of the printhead reduces the distance between the work and the printhead. Printing to the lower position is now made possible. The printhead with anti-corrosion plating keeps working in severe environment.

\* Corresponding models: For small characters and high-speed printing



Totally-new user interface!

Intuitive operations with a new readily-understandable screen design is now adopted. Most of the operations can be completed on one screen with a simplified and well-arranged design. Complicated operations are not required to obtain the necessary information thereby improving usability.



Troubleshooting and maintenance guides using plain illustrations

The necessary operations will be displayed on the screen using illustrations when the ink filter needs replacement or when troubleshooting or maintenance is needed. Comprehensive illustrations help to maintain the quality.

