



## Intermittent Coating Machine

Max. Size of coating : 150mm,  
GSM: 30 to 200,  
Max. Speed of coating : 15 mpm at 55 GSM.  
For higher GSM the max. speed will decrease,  
The max. melting capacity is 4 kg /hr. of this set.

M/c specifications:

1. Unwind: 2 station
  2. Coating Station: Slot Die coating (Chiller, water pump in your scope.)
  3. Lamination Nip
  4. Cutting Unit: 1 Station
- Controller by PLC and operated with HMI.  
5. Permelter: Tank capacity 5 Lit.  
6. Hot melt Hose. Length 2 m

DIMENSIONS: 5m x 1.5m x 1.5m  
Total Electrical Load: 7.5 KW

Watch  
Video



Watch  
Video



Hot melt Coating both side  
(Narrow web)

## Hot Melt Coating Machines



Watch  
Video



Hot Melt 2 side Coating  
with inline Printing

10,11 & 12 A, PARMAR INDUSTRIAL ESTATE,  
Kale Marg, Bail Bajar, Kurla, Mumbai, 400070. India.  
email: [info@trasyenterprises.in](mailto:info@trasyenterprises.in) website: [www.trasyenterprises.in](http://www.trasyenterprises.in)  
Contact : +91-9833077250



# TRASY

ENTERPRISES

## Hot Melt Coating Machines

Used for Making of :  
Double side tapes; Duct tapes; Double side foam  
adhesive tapes; Clean adhesive tapes; Masking  
adhesive tapes; Alu.foil tapes; Fabric tapes;  
Shoes material; Medical tapes; Trans Dermal  
Tapes, Sticker Label; Trademark Label; Film,  
Fabric, Textile, Paper & Lamination ...etc.