



BR 911E
6-10kVA
Online UPS



RAPSTECH™





Features:

- ❖ True Online Double conversion with **Advanced DSP and 3-level technology**.
- ❖ Active power factor correction (APFC), **Input Power Factor up to 0.99**.
- ❖ High efficiency 95% up to 98% on ECO mode.
- ❖ **Advanced Digital Parallel Technology (Upto 4 Units)**.
- ❖ **Wide Input Voltage Range and Frequency Range**.
- ❖ 50 / 60 Hz frequency auto sensing
- ❖ **Two modes of frequency conversion: 50 Hz input / 60 Hz output or 60 Hz input / 50 Hz output**
- ❖ Dual-Input Design, supporting independent bypass
- ❖ Flexible battery configuration (Settable 16 / 18 / 20 no's Batteries)
- ❖ Digitally controlled charger
- ❖ High charging current available (Max. 10 A)
- ❖ **Output power factor 0.9**
- ❖ **Fan Speed varies intelligently with temperature** to extending its service life.
- ❖ Compact Internal layout, Miniaturized the complete unit for **Small Footprint**.
- ❖ LCD+LED display, Multi-Functional keys operation.
- ❖ Effective software and hardware protection function, Robust Self-Diagnostic Function.

Multi-Platform Communications:

- ❖ Standard: RS232.
- ❖ Optional: USB, RS485 Card, Dry Contacts, SNMP Card, EPO function.

RAPSTECH™

Technical Specifications:

Model	BR 911E - 6kVA	BR 911E - 10kVA
Phase	1 Phase Input / 1 Phase Output	
Capacity	6000VA / 5400 W	10000VA / 9000 W
Input		
Input Wiring	Single Phase Three Wire (1Ø + N + PE)	
Rated Voltage	208 / 220 / 230 / 240 Vac	
Voltage Range	176 ~ 288 Vac	
Frequency	50 ~ 60 Hz (Auto Sensing)	
Frequency Range	40 ~ 70 Hz	
Power Factor	≥ 0.99 @ 100% load	
Bypass Voltage Range	-40% ~ +15% (Settable)	
Total Harmonic Distortion (THDi)	≤ 5%	
Output		
Output Wiring	Single Phase Three Wire (1Ø + N + PE)	
Rated Voltage	208 / 220 / 230 / 240 Vac	
Voltage Regulation	± 1%	
Frequency	Synchronized to Bypass in Main Mode; 50/60 Hz ± 0.1 Hz in Battery Mode	
Waveform	Sinusoidal	
Power Factor	0.9	
Total Harmonic Distortion (THDv)	≤ 1% (Linear Load); ≤ 4% (Non Linear Load)	
Crest Factor	3:1 (Max)	
Overload	105% ~ 110% for 10 min; 111% ~ 125% for 1 min; 126% ~ 150% for 30 s	
Battery		
DC Voltage	192 / 216 / 240 Vdc; 192 Vdc Default	
Number of Batteries	16 / 18 / 20; 16 no's Default	
Charging Current	Long backup model 5 A (default); 10 A (Max)	
System		
Efficiency	≥ 94% at 100% Load, max. 95% at 60% load, ≥ 98% in ECO mode	
Transfer Time	0 ms	
Protections	Short Circuit, Over Load, Over Temperature, Battery Low / High Voltage,	
Communications	RS232 (Standard), USB / RS485 / Dry Contact / SNMP / MODBUS (Optional)	
Display	LCD + LED	
Max. Number of Parallel Connections	4 units (Optional)	
Enivroment		
Operating Temperature	0°C ~ 40°C	
Storage Temperature	-25°C ~ 55°C (Without Batteries)	
Relative Humidity	0 ~ 95% (Non-Condensing)	
Altitude	≤ 1000 m, Derating 1% for Each Additional 100 m	
IP Rating	IP 20	
Noise Level @ 1m	≤ 55 DB	≤ 58 DB
Physical		
Dimensions (W X D X H) (mm)	191 X 465 X 350	191 X 495 X 350
Net Weight (kg)	14.5	16.5

* All specifications subject to change without notice



RAPSTECH™

 Plot No. 181, 11th Avenue, Dandamudi Enclave, Kompally Road, PetBasheerabad,
Rangareddy, Hyderabad - 500067 |  905 905 1725 |  Info@rapstech.co.in