

# VI911 Series

6 - 10 kVA Single Phase Rack UPS

More Than Power Backup – It's Power Assurance.





## VI911 Series

### 6~10kVA Single Phase Rack UPS

#### **⊗** Key Features

- DSP Technology True Online Double Conversion
  UPS Systems.
- IGBT Rectifier and IGBT Inverter.
- Active Input Power factor Near to Unity ≥0.99.
- · Intelligent battery management.
- 3-level topology, high performance and efficiency up to 95%.
- Output PF=1,high load adaptability.

- Wide range of input voltage tolerance.
- · Adapt to half-wave load.
- · Auto fault waveform recording.
- · Self-aging function to save test energy.
- 10kW in 2U, high power density.
- · Li-ion battery compatible.
- · All Monitoring features (Optional).

Model		VI911-6KLR	VI911-10KLR
Rate Power		6kVA/6kW	10kVA/10kW
Input voltage range		110~288VAC; 100% load@>176VAC; 90% load@>154VAC; 75% load@>132VAC; 50% load@>110VAC	
Input power factor		≥0.99	
Input Frequency range		40-70Hz	
Output power factor		Unity	
Output	Rate voltage	220/230/240VAC	
	Frequency	50/60Hz, self adaption	
	Load response	≤5% (0% - 100% -0%)	
	Recovery time	≤40ms (0% - 100% -0%)	
	THD	≤1%, linear load ;≤ 5% , non-linear load according to IEC62040-3	
Transfer time-Main to Battery		0ms	
Transfer time-INV to BYP		0ms	
Crest factor		3:1	
Battery type		External battery	
Battery Number		16-24 Nos Adjustable	
Battery voltage		Default 192VDC , Adjustable	
Max charging		12A	
Efficiency – normal mode		Up to 95%	
Noise (1 meter)		<58dB	
Overload Normal mode ECO mode		105%~110%: 10mins,111%~125%: 1 min,126%~150%: 30 seconds	
		<125%: Long time,126%~130%:5mins,131%~150%:1min,>150%:200ms	
Communication		RS232, EPO, RS485	
Optional		SNMP card, AS400, USB	
Dimension W*D*H(mm)		440*580*86 (2U)	
Weight(kg)		16	18

<sup>\*</sup>Product specifications are subject to change without further notice.



info@rapstech.co.in www.rapstech.co.in +91 905 905 1725, +91 9000 374 695