

AUTOMATIC TILT - BACK/RFT TYRE CHANGERS/LEVERLESS MOUNTING TOOL



T 705

Technical Specification



Outer Clamping
Size
12"-26"



Inner Clamping
Size
10"-24"



Max. Wheel Dia. 1040mm



Max. Wheel Width
3"~15"



Bead breaking
Force
2700 KG



Operating Pressure
8~10 BAR



Power Supply
220V/50HZ/1PH



Motor Power
1.5HP

OPTIONAL LEVERLESS MOUNTING TOOL



T 705 H



ALINER
AUTOMOTIVE
THE 3D WHEEL ALIGNMENT LEADER ...

AUTOMATIC TILT - BACK/RFT TYRE CHANGERS/LEVERLESS MOUNTING TOOL

T 705/T 705H TECHNICAL FEATURES

- ▶ Automatic tyre changer with pneumatic tilt-back tower.
- ▶ Robust 041 mm hexagon shaft.
- ▶ Simultaneous pneumatic locking of the horizontal and vertical arms with automatic positioning of the head in the optimal work position.
- ▶ Tools head with interchangeable plastic inserts for rim protection.
- ▶ Pneumatic tilting arm support column featuring high torsional rigidity in all operation positions.
- ▶ Clockwise and anticlockwise rotation of the turntable through electric motor.
- ▶ The pedal assembly can be removed allowing easy servicing.
- ▶ Protection kit for bead breaker shoe, demounting head, clamping jaw and lever comes standard.
- ▶ Independent tire inflation bay with inflation tube, pressure gauge and pressure release button.
- ▶ Complete with lubrication filter and pressure regulator.

T 705H DP20 HELPER ARM :

- ▶ Rotating arm with bead pressing block for drop-center rims, to assist fitting and removal of tyres, particularly low profile tyres.
- ▶ Rim pressing cone for assisting wheel clamping.
- ▶ Tyre lifting disk to aid in demounting difficult tyre and wheel combinations.
- ▶ Mid-position roller helps loosening of the second bead.

T 705 TECHNICAL DETAILS



Stainless tool head with interchangeable plastic inserts to protect rims.



Independent tire inflation bay with inflation tube, pressure gauge and pressure release button.



Premium quality pressure regulator with water filter and lubricator.



Powerful bead breaker with 2700kg capacity.



Extractable pedal assembly for easy maintenance



Self-centering four-jaws with double pneumatic cylinder for secure clamping of all rim types.



Simultaneous pneumatic locking of horizontal and vertical head arms, with automatic head positioning in the ideal working condition.



Optional bead seater (tubeless inflator)

T 705H TECHNICAL DETAILS



Stainless tool head with interchangeable plastic inserts to protect rims.



Independent tire inflation bay with inflation tube, pressure gauge and pressure release button.



Simultaneous pneumatic locking of horizontal and vertical head arms, with automatic head positioning in the ideal working conditions.



Powerful bead breaker with 2700kg capacity.



Extractable pedal assembly for easy maintenance



Right helper arm with bead pressing roller, tire lifting disk and bead pressing head.



Premium quality pressure regulator with water filter and lubricator.



Self-centering four-jaws with double pneumatic cylinder for secure clamping of all rim types.

Standard Accessories



Tyre Paste Container



Paste Brush



Tool Head Protection



Bead Breaker Protection



Claw Protection



Tyre Lever

ALINER AUTOMOTIVE EQUIPMENTS PVT. LTD.

Office No. 309, E-Block, DDA Market, Vikas Puri,
New Delhi, INDIA-110018
Ph. : 011-40367737; Mobile : 9811257753



www.automotiveequipmentsindia.com
www.3dwheelalignmentmachine.com



/alinerautomotiveequipments



/alinerautomotive



alinerindia@yahoo.com/salesaliner@gmail.com

THE 3D WHEEL ALIGNMENT LEADER ...
ALINER
AUTOMOTIVE