

PORTABLE PNEUMATIC HAND PUMP

MODEL: HP 04A



INTRODUCTION

Exact pressure measurement and monitoring are must in applications crucial to operational safety of machinery and industrial installations.

Regular inspection of the pressure gauges / sensor / transmitters / indicators used in these applications is absolutely essential for economic and technical - safety reasons and is already prescribed as obligatory in many sectors.

APPLICATIONS

- ☐ Energy Production and energy Distribution sectors
- ☐ Glass, Ceramic, Semi conductor industries
- $f \Box$ Steel material processing industries
- ☐ Calibrators laboratories etc.,.

Technical Specifications

Features	Values
Model	HP 04A
Pressure medium	Dry air
Pressure range	-0.85 to 2 bar
Ref Inst. Connection	4mm nylon Hose with ¼" BSP (F) adapter
Process Connection	¼" BSP (F) adapter
Main Pump	Ergonomic scissor handle
Fine Pressure Adjustment	Vernier Value
Pressure relief valve	Vent knob
Pressure / vacuum selector	Button valve (pin)
Pump dimension in mm (Appox.)	170 x 45 (Height x Dia)
Weight	800 gms (Approx.) (except accessories)

Note: Due to continuous product improvements, Published specifications may change with out notice

Standard Delivery

- **Basic Instrument** 1.
- 1 meter long 4mm nylon Hose with 14" BSP (F) adapter 2.
- Swivel Adapter with 'o' Ring- 1 no
- Spare seal kit 1 set
- Standard adopter set 10 pieces set
- 6. Instruction manual
- 7. **Test certificate**

Optional

1. Carrying case



Carrying case



SANSEL INSTRUMENTS AND CONTROLS SANSEL CALIBRATION LABORATORIES

ISO/IEC 17025 Accredited Calibration Laboratory by NABL CC - 2879 (Thermal, Mechanical, Electro-Technical, Dimension Parameters)

1 / 46 , 3rd Main road, Ganga Nagar, MMDA Colony , Maduravoyal , Chennai - 600 095. INDIA 🕿 +91 44 2378 3951, 🖠 +91 72999 72085 / 86 / 93, 🖠 +91 98401 49928 ⊠ enquiry@ sansel.net



www.sansel.in

www.sansel.co.in

www.calibrators.in

