



**PRINT WITH PRECISION,
EVERY TIME**

RICHO GEN6 (8/16/32 HEAD)



Product mode	KTL 1816/ KTL 2616
Model	8 Head / 16 Head / 32 Head
Effective print width	1800/2200/2600 mm
Speed	240 Metres/Hour (16 Heads)
Maximum printing resolution	2400 DPI
Printing part introduction	Automatic negative pressure ink supply, automatic car liftin, automatic positive pressure cleaning, automatic moisturising, sprinkler anti- collision system
RIP Software	Neostampa/ Texprint
Main Ink Tank / Ink 8 Colors	10L / C, M, Y, K, O, R, G, B
Belt system introduction	Authentic drying and winding system, automatic cleaning guide belt system, anti- pressure roller print, synchronous pressure roller
Dryer unit	Single-layer tunnel oven (optional steam configuration)
Ink type	Reactive/disperse/acid/pigment ink
Print head height	Height adjustable 15-30mm to adapt medium of difference thickness
Power voltage	380V, 3L+N+G(with independent reliable effective earth wire)
Power Consumption	Print 16KW, Oven 20KW (steam oven 4KW)
Workshop Condition	Temperature:20-30C, humidity: 50-65%

Effective width

	1800mm	2200mm (Effective width 2180mm)	2600mm
Printer	4165mm*2200mm*1600mm (L*W*H)	4165mm*2200mm*1700mm (L*W*H)	5195mm*2200mm*1750mm (L*W*H)
Dryer	2555mm*2150mm*1670mm (L*W*H)		
Ink Cabinet	1900mm*700mm*1000mm (L*W*H)		
Weight	Printer: 3100kg	Printer: 3800kg	Printer: 5000kg

8 HEAD SUBLIMATION PRINTER



Name	8 HEAD HIGH DIGITAL PRINTING
Model	8 Head
Printing Speed/Mode	1 Pass 220 MT/H
Print Head & Quantity	13200 8 pcs
Print Head Width	1.9 M
RIP Software	NEO STEMPA
Temperature/Humidity	Temp: 20-30C, Humidity: 45-65%
Power	Power: 230W, External drying: 2400w
Wiring	63A MCB One piece 16 A Socket 4 piece 10 mm copper cable
Dimension (L*W*H)	12x4x5 feet

16 HEAD SUBLIMATION PRINTER



Name	16 HEAD HIGH DIGITAL PRINTING
Model	16 Head
Printing Speed/Mode	1 Pass 450 MT/H
Print Head & Quantity	13200 16 pcs
Print Head Width	1.9 M
RIP Software	NEO STEMPE
Ink Tank	10Ltrs with Negative Pressure
Temperature/Humidity	Temp: 20-30C, Humidity: 45-65%
Power	Power: 230W, External drying: 5 KW
Wiring	63A MCB One piece 16 A Socket 4 piece 10 mm copper cable
Dimension (L*W*H)	13.5x5.5x5.5 feet

24 HEAD SUBLIMATION PRINTER



Name	24 HEAD HIGH DIGITAL PRINTING
Model	24 Head Industrial Body
Printing Speed/Mode	1 Pass 750 MT/H
Print Head & Quantity	13200 24 pcs
Print Head Width	1.9 M
Take up motor	10,000 Mtr roll (Industrial body)
Ink Tank	10Ltrs with Negative Pressure
RIP Software	NEO STEMPEA
Temperature/Humidity	Temp: 20-30C, Humidity: 45-65%
Power	35 kW, 3 Phase, 5 line output
Dimension (L*W*H)	16x12x6 feet

HEAT TRANSFER MACHINE



PRODUCT FEATURES:

- Auto oiling system
- 100% Nomex blanket ensures natural fabric hand feel.
- Blanket sensor to control the blanket
- 2 metre table for proper adjustment of fusing

Wiring - 50 mm cable - 4 core copper wire
250 A MCB 4 Pole

Specification:

Drums Size	600 mm	800 mm	1000 mm
Power	42kw	63kW	73kw
Temp Range	0-399	0-399	0-399
Speed	300MT/ HR	600MT/HR	800MT/HR
Dimension (L*W*H)	8x9x7 feet	9x10x8 feet	9x10x8 feet

HEAT TRANSFER MACHINE WITHOUT BUTTER PAPER



PRODUCT FEATURES:

- Auto oiling system
- 100% Nomex blanket ensures natural fabric hand feel.
- Blanket sensor to control the blanket
- 2 metre table for proper adjustment of fusing

Wiring - 50 mm cable - 4 core copper wire
250 A MCB 4 Pole

Specification:

Drums Size	600 mm	800 mm	1000 mm
Power	42kw	63kW	73kw
Temp Range	0-399	0-399	0-399
Speed	300MT/ HR	600MT/HR	800MT/HR
Dimension (L*W*H)	8x9x7 feet	8x10x17 feet	8x10x17 feet



SUBLIMATION INK

HD Ink, Super HD Ink,
Fluorescent Ink

Packing 1 ltr & 5 Ltrs

SUBLIMATION PAPER

Quality	GSM
Indian	45/55 gsm & above
Chinese	29 gsm
Size	36,40,42,44,46, 48,50,58,60,63



SINCE 2005

DIGITAL SOLUTIONS PVT LTD

CONTACT US:

Address: U/9 & 10, Ashirwad Square, Near Sosyo Circle,
Udhna Magdala Road, Surat, Gujarat

Phone : +91 98980-19900 | +91 99256-26031 | +91 96876-90000

Website : www.ktldigitalsolutions.com

Email: kdspvtltd9@gmail.com

DIRECT PRINTER INK

Reactive Ink, Disperse Ink,
Pigment Ink C,M,Y,K,O,R,G,B

Packing 5 Ltrs

