

TACHOMETER CALIBRATOR

MODEL : RPMC 1700 - 2A



INTRODUCTION

The RPMC 1700 Series is high precision Tachometer calibrator, generates true reference rotation per minute (RPM). This calibrator uses “German technology” with high speed motor, high precision encoder and adoption of a new power full 32 bit CPU in control drive, featuring automated gain tuning function, stability, stable stop, rugged in use and many more. Due to it's light weight and rugged Aluminium enclosure, it is suitable for in-house and on-site calibration of contact / non contact Tachometer, Tacho coil, Tacho generator, RPM indicator, RPM transmitter, Speedo meter, Proximity sensor, Stroboscope, etc.,.

FEATURES

- ✓ 4.3" True colour TFT display with Touch screen
- ✓ Low noise
- ✓ Quick settling time
- ✓ Better stability
- ✓ Any odd value is settable for both contact & Non - contact RPM
- ✓ High resolution
- ✓ Ultra stable motor with high precision encoder and drive
- ✓ Direct drive shaft (there is no gear)
- ✓ Compact size

technical Specifications

Model	RPMC 1700 - 2A
Display	4.3" True colour TFT LCD Display with Touch screen
Control Range	Contact : 0 to 6000 RPM Non Contact : 0 to 1,02,000 RPM
Resolution	0.1 RPM
Accuracy	Contact : 6 rpm to 6000 rpm = $\pm 0.007\%$ of rdg + 0.1 rpm, Non Contact : 1 Teeth : 6 rpm to 6000 rpm = $\pm 0.007\%$ of rdg + 0.1 rpm 5 Teeth : 6001 rpm to 30,000 rpm = $\pm 0.007\%$ of rdg 17 Teeth : 30,001 rpm to 1,02,000 rpm = $\pm 0.007\%$ of rdg
Display Stability	± 0.1 RPM (for both Contact & Non Contact)
Stability	Contact : ± 0.1 rpm Non Contact : 1 Teeth : 6 rpm to 2000 rpm = ± 0.1 rpm 2001 rpm to 6000 rpm = ± 0.2 rpm 5 Teeth : 6001 rpm to 30,000 rpm = better than ± 0.7 rpm 17 Teeth : 30,001 rpm to 1,02,000 rpm = better than ± 1.0 rpm
Stability Time	Within 5 seconds
Noise level	< 50dB
Motor	Ultra stable motor with high resolution Encoder & Drive
Power supply	230V AC $\pm 10\%$ / 50Hz (Optional 110V AC)
Power Consumption	750 VA
Outer Enclosure Construction	Aluminium Anodised
Overall Dimension	260mm L x 440mm W x 230mm H (Approx.)
Instrument Weight	13 kg(Approx.)

Standard Delivery

1. Basic Instrument
2. Spare fuses
3. Instruction manual
4. Mains cord
5. Traceable calibration certificate

Optional

1. Master Tachometer
2. Additional Reflection stickers
3. Carrying case



Carrying case



SANSEL INSTRUMENTS AND CONTROLS SANSEL CALIBRATION LABORATORIES LLP

ISO/IEC 17025 Accredited Calibration Laboratory by NABL CC - 2879
(Thermal, Mechanical, Electro-Technical, Dimension Parameters)

1 / 46 , 3rd Main road, Ganga Nagar, MMDA Colony , Maduravoyal , Chennai - 600 095. INDIA
☎ +91 44 2378 3951, 📞 +91 72999 72085 / 86 / 93, 📠 +91 98401 49928 ✉ enquiry@ sansel.net

🌐 www.sansel.net

🌐 www.sansel.in

🌐 www.sansel.co.in

🌐 www.calibrators.in

