

# TACHOMETER CALIBRATOR

MODEL : RPMC 1700 - 3A



## INTRODUCTION

The RPMC 1700 Series is high precision Tachometer calibrator, generates true reference rotation per minute (RPM). This calibrator uses “German technology” with high speed motor, high precision encoder and adoption of a new power full 32 bit CPU in control drive, featuring automated gain tuning function, stability, stable stop, rugged in use and many more. Due to it's light weight and rugged Aluminium enclosure, it is suitable for in-house and on-site calibration of contact / non contact Tachometer, Tacho coil, Tacho generator, RPM indicator, RPM transmitter, Speedo meter, Proximity sensor, Stroboscope, etc.,.

## FEATURES

- ✓ 7" True colour TFT display with Touch screen
- ✓ Low noise
- ✓ Quick settling time
- ✓ Better stability
- ✓ Any odd value is settable for both contact & Non - contact RPM
- ✓ High resolution
- ✓ Ultra stable motor with high precision encoder and drive
- ✓ Direct drive shaft (there is no gear)
- ✓ Compact size

# Technical Specifications

Model	RPMC 1700 - 3A
Display	7" True colour TFT LCD Display with Touch screen
Control Range	Contact : 0 to 8000 RPM Non Contact : 0 to 1,20,000 RPM
Accuracy	Contact : 6 rpm to 4000 rpm = $\pm 0.005\%$ of rdg + 0.1 rpm 4001 rpm to 8000 rpm = $\pm 0.005\%$ of rdg Non Contact : 1 Teeth : 6 rpm to 4000 rpm = $\pm 0.005\%$ of rdg + 0.1 rpm 4001 rpm to 8000 rpm = $\pm 0.005\%$ of rdg 5 Teeth : 8001 rpm to 40,000 rpm = $\pm 0.005\%$ of rdg 17 Teeth : 40,001 rpm to 1,36,000 rpm = $\pm 0.005\%$ of rdg
Resolution	0.001 RPM
Display Stability	Contact: $\pm 0.002$ RPM, Non Contact: $\pm 0.01$ RPM
Stability	Contact: $\pm 0.1$ rpm, Non Contact: 1 Teeth : 6 rpm to 4000 rpm = $\pm 0.1$ rpm 4001 rpm to 8000 rpm = $\pm 0.2$ rpm 5 Teeth : 8001 rpm to 40,000 rpm = better than $\pm 0.5$ rpm 17 Teeth : 40,001 rpm to 1,36,000 rpm = better than $\pm 0.8$ rpm
Stability Time	Within 5 seconds
Noise level	< 50dB
Motor	Ultra stable motor with high resolution Encoder & Drive
Power supply	230V AC $\pm 10\%$ / 50Hz (Optional 110V AC)
Power Consumption	750 VA
Outer Enclosure Construction	Aluminium Anodised
Overall Dimension	260mm L x 440mm W x 230mm H (Approx.)
Instrument Weight	13 kg(Approx.)

Note: Due to continuous product improvements, Published specifications may change with out notice

## Standard Delivery

1. Basic Instrument
2. Spare fuses
3. Instruction manual
4. Mains card
5. Traceable calibration certificate

## Optional

1. Master Tachometer
2. Additional Reflection stickers
3. Carrying case



Carrying Case



## SANSEL INSTRUMENTS AND CONTROLS SANSEL CALIBRATION LABORATORIES LLP

ISO/IEC 17025 Accredited Calibration Laboratory by NABL CC - 2879  
( Thermal, Mechanical, Electro-Technical, Dimension Parameters )

1 / 46 , 3<sup>rd</sup> Main road, Ganga Nagar, MMDA Colony , Maduravoyal , Chennai - 600 095. INDIA  
☎ +91 44 2378 3951, 📞 +91 72999 72085 / 86 / 93, 📠 +91 98401 49928 ✉ enquiry@ sansel.net

