

**VITAL TECHNICAL SDN. BHD.**

Technical Data Sheet

**VT-422
UltraBand**

Issuance date: 10/09/2022

Revision date: -

Revision No.: 22-01

VT-422 UltraBand

Butyl Flashing Tape

APPEARANCE

Grey tape

ROLL WIDTH50mm, 75mm, 100mm,
150mm, 300mm**THICKNESS**

1.2mm

PACKAGING50mm x 2.5m x 1.2mm /
roll*(6 rolls/ inner, 48 rolls/ carton)*50mm x 5m x 1.2mm /
roll*(6 rolls/ inner, 36 rolls/ carton)*50mm x 10m x 1.2mm /
roll*(6 rolls/ inner, 36 rolls/ carton)*75mm x 5m x 1.2mm /
roll*(4 rolls/ inner, 24 rolls/ carton)*75mm x 10m x 1.2mm /
roll*(4 rolls/ inner, 24 rolls/ carton)*100mm x 5m x 1.2mm
/ roll*(3 rolls/ inner, 18 rolls/ carton)*100mm x 10m x 1.2mm
/ roll*(3 rolls/ inner, 18 rolls/ carton)*150mm x 5m x 1.2mm
/ roll*(2 roll / inner, 12 rolls/ carton)*150mm x 10m x 1.2mm
/ roll*(2 roll / inner, 12 rolls/ carton)*300mm x 5m x 1.2mm /
roll*(6 rolls/ carton)*300mm x 10m x 1.2mm
/ roll*(6 rolls/ carton)***SHELF LIFE**

24 months

STORAGEStore under cover, in dry
and cool place with
temperature below
30 °C. Protect from
freezing.**SERVICE****TEMPERATURE**

-15 °C – 80 °C

DESCRIPTION

VT-422 Ultraband is a Butyl self-adhesive waterproof sealing tape that grips on tight and bonds instantly. It's a premium quality waterproofing material that can be applied on most surfaces, providing strong adhesive force, no shrinkage, excellent UV resistance and water resistance.

With its easy-to-apply feature, VT-422 UltraBand is one of the best choices for construction and industrial applications as well as household repair.

TECHNICAL DATA	Special Gravity	: 1.8 – 2.5 g/mL
	Elongation	: ≥300%
	Tension	: ≥200 N/5cm
	Peel strength	: ≥5.25 N/cm

FEATURES	<ul style="list-style-type: none">▪ Easy to apply & strong instant bonding▪ Bond with most materials▪ No Shrinkage, without solvent▪ Excellent UV & water resistance
-----------------	---

APPLICATION	<ul style="list-style-type: none">▪ Roof: roof water resistance, repair roof leaking, over joints and cracks in roof cladding.▪ Interior: water tank, doors, walls, bathroom, swimming pool, ventilation pipe, PVC pipe.▪ Exterior: apply over joints and cracks on cement sheeting, masonry tiles, around water pipes, gutters, down pipes and more.▪ Car industry: repair for leaking on the roof and car body.
--------------------	--

PREPARATION	1. The application surfaces must be clean, dry, and free of dirt, grease, oil or water.
--------------------	---

APPLICATION DIRECTION	<ol style="list-style-type: none">1. Unroll only the required length, and cut the tape to the desired length.2. Remove the release sheet and apply the tape on the application surfaces.3. Press it into position using fingertip pressure or a roller to smoothen the surface to avoid creases or air pockets.4. Overlap at least 30mm is required to achieve a better outcome.
------------------------------	---

CAUTION	Keep out of reach of children. Safety data sheet available on request. For further health and safety information, consult the latest safety data sheet.
----------------	---

LEGAL NOTES	Every endeavour has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for the loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.
--------------------	---