

Water Bath



RWB 6

REMI Water Bath is multipurpose water bath with adjustable double line six holes to hold different size samples for easy & hygienic heating. RWB provides precise and constant temperature helps achieving uniform heating for the samples.

Salient Features:

- Microprocessor control with timing function
- Digital display
- Audible and visual alarm for over temperature

| Technical Data | |
|--------------------------------|--------------------------|
| Parameter | RWB 6 |
| Temperature range | RT \pm 5°C ~99°C |
| Temperature stability | \pm 0.5°C |
| Tracking alarm | \pm 2°C |
| Chamber volume | 15 Ltrs |
| Interior Dimension (WxDxH, mm) | 450x300x110 |
| Timing range | 1~999 min. |
| Remark | Double lines six holes |
| Electrical requirements | 220V, 50Hz, Single phase |
| Power Consumption | 1500W |

Supply: 220-240 Volts, 50 Hz Single Phase. -

Water Bath Shakers



Water Bath Shaker RSB - 12

These Water bath Shakers have wide applications in Biotechnology, Micro - Biology, Chemistry, Quality Control and other life sciences laboratories.

These units are double walled with exterior body and inner chamber of stainless steel having effective insulation in between. The stainless steel bath has size of 355 mm (W) x 300 mm (D) x 165 mm (H). A special pyramid type cover provided avoids evaporation of water and makes condensed water to fall back in the bath. A cock is provided to facilitate draining of Bath contents.

The removable stainless steel tray houses lotus clamps for variety of flask capacities. Standard unit supplied with tray accommodating 12 flasks x 100 ml. while trays with the following capacity are available optionally.

| | |
|--------------------|-------------------|
| 50 ml x 12 flasks | 150 ml x 9 flasks |
| 250 ml x 6 flasks | 500 ml x 4 flasks |
| 1000 ml x 2 flasks | 2000 ml x 1 flask |
| Test Tube racks | |

Salient Features :

- Inner chamber and outer body of SS 304
- Heating up to 95°C
- Digital Temperature Indicator cum Controller with precise accuracy of \pm 1°C
- Shaking speed range from 40 to 180 strokes per min
- Stroke length 25 mm